

## 產品編號：KL-220 ■ 透明流展中塗

## Solvent-Free Clear Spreading of Epoxy Middle Coating

- KL-220是高強度環氧樹脂，高物性、高強度，施工容易，無刺激味道，適用於地床之中塗樹脂砂漿及流展中塗。
- KL-220 is high strength non solvent Epoxy resin, easy for working, high tensile, and high physical property, suitable for middle coating of the ground, mortar resin and spreading middle coating.

### 用途 APPLICATION

- 食品廠、電子廠、GMP藥廠、無塵室、倉庫、保養場、學校、停車場、機械廠、五金工廠、醫院、大賣場、大樓地下室等地坪工程之塗裝。
- Food-stuff factory、Electronic factory、GMP pharmaceutical factory、Dust-free room、warehouses、service factory、school、parking area、machine processing plants、metal works、hospital、supermarket、underground on floor coatings.

### 特性

- 耐酸鹼、耐溶劑性等優異。
- 接著性優異，不龜裂、不剝落。
- 耐磨耗性優異。

### CHARACTERISTICS

- Excellent acid, alkali resistance and solvent resistance .
- Excellent adhesion for cement, non cracking and non peel.
- Excellent wear resistance.

### 技術資料

### Technical data

顏色	主劑:透明	硬化劑:褐色	Color	Base:Clear	Hardener:Brown
配合比	2:1		Mixing ratio	2:1	
包裝量 主劑(kg)	20		Packaging Resin(kg)	20	
硬化劑(kg)	10		Hardener(kg)	10	
可使用時間(min)	20(25°C)		Pot life(min)	20(25°C)	
硬化時間(hr)	8(25°C)		Full Hard(hr)	8(25°C)	

## 產品編號：KL-225 ■ 流展砂漿中塗

## Solvent-free Leveling Epoxy Intermediate Coat

- KL-225是高強度環氧樹脂，高物性強度，施工容易，適用於地床之流展中塗。
- KL-225 is tough epoxy resin with good physical properties and suitable for the intermediate coat for floor coating.

### 用途 APPLICATION

- 食品廠、電子廠、GMP藥廠、無塵室、倉庫、保養場、學校、停車場、機械廠、五金工廠、醫院、大賣場、大樓地下室等地坪工程之塗裝。
- Floor Coating for cement structure such as foodstuff factory, electronics factory, GMP pharmaceutical factory, cleanroom, warehouse, automobile repair shop, school, parking lot, machinery plant, hospital, hypermarket, underground.

### 特性

- 耐酸鹼、耐溶劑性等優異
- 接著性優異,不龜裂、不剝落
- 耐磨耗性優異

### CHARACTERISTICS

- Excellent acid, alkali, and solvent resistance
- Excellent adhesion without cracking or peeling
- Excellent wear resistance

### 技術資料

### Technical data

顏色	主劑:各色	硬化劑:微黃	Color	Base:Various colored menu	Hardener:Yellow brown liquid
配合比	5:1		Mixing ratio	5:1	
包裝量 主劑(kg)	20		Packaging Resin(kg)	20	
硬化劑(kg)	4		Hardener(kg)	4	
可使用時間(min)	20(25°C)		Pot life(min)	20(25°C)	
硬化時間(hr)	8(25°C)		Full Hard(hr)	8(25°C)	