

Epoxy地床系列產品

建築類系列產品

防蝕系列產品

## 產品編號：KL-234

## ■ 有色耐酸鹼流展面塗

## Acid, Alkali-Resistance Spreading Colorful of Epoxy Top Coating

- KL-234 有色無溶劑型環氧樹脂面塗，是採用100%環氧樹脂，搭配特殊硬化劑精製而成，其硬化後之塗膜耐酸鹼性優異，適用於耐酸鹼地床材料之面塗。
- KL-234 is Solvent-free Epoxy resin, and it has excellent glossy surface after hardening. the construction also can be done. It is most suitable for surface coating for acid and alkali- resistance ground .

## 用 途USAGE

- 針對要求耐酸鹼度高之食品廠、電子廠、GMP藥廠、無塵室、倉庫、機械廠、化學工廠等地坪工程之塗裝。
- Food-stuff factory, Electronic factory, GMP pharmaceutical factory, Dust-free room, warehouses, machine processing plants, metal works floor coating.

## 特性

- 耐酸鹼、耐溶劑等特優。
- 接著性優異，不龜裂、不剝落。
- 耐磨耗性優異。

## CHARACTERISTICS

- Excellent acid resistance 、alkali resistance and solvent resistance .
- Excellent adhesion for cement. non creaking and non peel.
- Excellent wear resistance.

## 技術資料

## Technical data

顏色	主劑:特殊色	硬化劑:透明	Color	Resin: special color	Hardener : Clear
配合比	4 : 1		Mixing ratio	4 : 1	
包裝量 主劑 (kg)	20		Packaging Resin(kg)	20	
硬化劑 (kg)	5		Hardener (kg)	5	
可使用時間 (min)	15 (25°C)		Pot life (min)	15(25°C)	
硬化時間 (hr)	8 (25°C)		Full Hard (hr)	8(25°C)	

## 產品編號：KL-280 ■ 透明耐酸鹼流展面塗

## Transparent Acid, Alkali-Resistance Spreading of Top Coating

- KL-280透明無溶劑型環氧樹脂面塗，是採用100%環氧樹脂，搭配特殊硬化劑精製而成之透明面塗，其硬化後之塗膜耐酸鹼性優異，適用於耐酸鹼地床材料之塗裝。
- KL-280 Solvent-free Epoxy resin, and it has excellent glossy surface after hardening. the construction also can be done. It is most suitable for surface coating for acid and alkali resistance ground .

## 用 途USAGE

- 針對要求耐酸鹼度高之食品廠、電子廠、GMP藥廠、無塵室、倉庫、機械廠、醫院、化學工廠等地坪工程之塗裝。
- Food-stuff factory, Electronic factory, GMP pharmaceutical factory, Dust-free room, warehouses, machine 、hospital 、chemical factory floor coating.

## 特性

- 耐酸鹼、耐溶劑等特優。
- 接著性優異，不龜裂、不剝落。
- 耐磨耗性優異。

## CHARACTERISTICS

- Excellent acid resistance 、alkali resistance and solvent resistance .
- Excellent adhesion for cement, non creaking and non peel.
- Excellent wear resistance.

## 技術資料

## Technical data

顏色	主劑:透明	硬化劑:透明	Color	Resin: Clear	Hardener : Clear
配合比	2:1		Mixing ratio	2 : 1	
包裝量 主劑 (kg)	20		Packaging Resin(kg)	20	
硬化劑 (kg)	10		Hardener (kg)	10	
可使用時間 (min)	15 (25°C)		Pot life (min)	15(25°C)	
硬化時間 (hr)	8 (25°C)		Full Hard (hr)	8(25°C)	